



GRAND CINEMA SUNSHINE IKEBUKURO, JAPAN

Product Specifications

- Structure
- Structure with prongs to set proper backrest angle, ranging from 20° to 37°.
 - Seat pan articulation system by patented blade system. Especially silent soft close tip-up, no maintenance required.
- Backrest and Seat
- Ergonomic form with good lumbar support.
 - Double curved structure in rigid material (class M3), inclusive of casing to allow fitting onto pedestal.
 - Polyurethane foam, cold moulded, density of 45 kg/m³.
 - Seat is of polyurethane fire retardant foam, cold-moulded, density of 60 kg/m³, moulded onto a metal support.
- Panel / Armrest
- Internal wooden structure with polyurethane foam, density 118 kg/m³
- Fire Resistance
- Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.
 - Other regulations such as EN 1021, BS 7176, BS5852 – upon request.
- Warranty
- Refer to QGR product warranty.
- Options
- Cupholder
 - Seat numbering
 - Row lettering
 - Embroidery logo
 - K-Roll castor system.
- Metal and Fabric Finishing
- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
 - All metal parts are with matte black finish of at least 60 microns, for indoor use.
 - Back and seat upholstery fabric with 3mm foam backing, finished with netting 15 g/m³.
 - Backrest and seat covers equipped with zippers.