



FERCO SEATING ILLUSTRATION ONLY

Product Specifications

Structure

- Combination of a wooden frame and a steel frame, upholstered with polyurethane High Resistance foam and polyester then, covered with fabric / leatherette / leather.

Backrest and Seat

- Inner back frame is made of plywood frame upholstered with polyurethane HR foam of 150 – 170mm thickness then, covered with fabric / leather / leatherette.
- Seat unit with 18mm compressed plywood fully upholstered with polyurethane HR foam of 120 – 130mm thickness then, covered with fabric / leather / leatherette.

Panel

- Wooden Panel topped with cupholder and covered with fabric / leather / leatherette.

Metal Finishing

- Zigzag lever systems that ensure the backrest and footrest are being operated smoothly.
- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish minimum of 60 microns for outdoor use.

Upholstery Material

- Refer to Ferco standard fabric/leatherette/leather charts.

Safety

- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations. in their last issues and particularly with safety regulations.
- Finger Proof - Recliners are attached with finger guards to reduce hazards.

Warranty

- Refer to Ferco product warranty.

Options

- Gooseneck Light
- Row Lettering.
- Seat Numbering
- Swivel Table / Smart Swivel Table / Double Action Swivel Table.
- Logo Embroidery.
- USB Charging Port
- Auto Return
- Lift-up Mechanism (easy lift system).
- Call System Button.
- By Pass Switch
- Privacy Panel.
- Flammability compliance with BS 5852 : 2006 section 3 ignition source 5.