



FERCO SEATING ILLUSTRATION ONLY

Product Specifications

Structure

- Structure with adjustable prongs which receives the backrest and a support for the seat.
- Possible depth adjustment.

Backrest and Seat

- Backrest with inner ply made of 15mm thickness plywood, upholstered with fabric / leather / leatherette.
- Seat unit with inner ply made of 18mm thickness plywood covered with foam of 70~105mm thickness and upholstered with fabric / leather / leatherette.
- Upholstered with padded cover on backrest, and headrest with modern design and shape.

Armrest, Panel & Leg

- Fixed, shared armrest with a designer cupholder.
- Top part made of HR foams and covered with fabric / leather / leatherette.
- Decorative aisle panel made of wooden ply and upholstered
- with fabric / leather / leatherette covers.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with Galvanized finish or an epoxy finish of at least 60 microns for outdoor use.

Upholstery Material

- Refer to Ferco standard fabric/leatherette/leather charts.

Safety

- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.

Warranty

- Refer to Ferco product warranty.

Options

- Aisle lighting with illuminated row letter.
- Oval row letter plate.
- Embroidered seat number.
- Logo embroidery.
- Leg cover.
- Fixed Table Top
- Flammability compliance with BS 5852 : 2006 section 3 ignition source 5.