



FERCO SEATING ILLUSTRATION ONLY

Product Specifications

Backrest

- Glided Backrest (with Headrest) with inner structure made of Ø19mm x thk 2.0mm metal frame upholstered with polyurethane HR foam then, covered with fabric / leather / leatherette. Topped with backrest and headrest paddings made from HR Foam and covered with fabric / leather / leatherette.

Seat

- Glide seat unit with inner structure made of Ø19mm x thk 2.0mm metal frame fully upholstered with foam of 120 - 130mm thickness and covered with fabric, also topped with seat padding made from HR foam and covered with fabric / leather / leatherette.

Armrests, Panel & Leg

- Fixed, shared armrest with a designer cupholder.
- Top part made of HR foams and covered with fabric / leather / leatherette.
- Decorative aisle panel made of wooden ply and upholstered with fabric / leather / leatherette covers.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with Galvanized finish or an epoxy finish of at least 60 microns for outdoor use.

Upholstery Material

- Fabrics - Refer Ferco Standard Fabrics Chart
- Leatherette - Refer Ferco Standard Leatherettes Chart
- Leather - Refer Ferco Standard Leathers Chart

Safety

- Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.

Warranty

- Refer to Ferco product warranty.

Options

- Aisle lighting with illuminated row letter.
- Oval row letter plate.
- Embroidered seat number.
- Logo embroidery.
- Leg cover.
- Flammability compliance with BS 5852 : 2006 section 3 ignition source 5.

Durability Test

- The gliding mechanism of the seat is in accordance to European Standard EN12727:2016 for combined seat and back durability test (as reference).