



TOA SAMUTPRAKARN, THAILAND

Product Specifications

Backrest

- Injection moulded co-polypropylene.
- UV Inhibitors are added at a rate to ensure no significant colour or plastic deterioration for a period of five (5) years.
- Back is free of fasteners and capable of accepting upholstery pad.
- Back pad is constructed of injection moulded polypropylene inner (typical wall thickness 3.5mm) with a 30mm polyurethane foam covering and upholstered with fabric or leatherette.

Seat

- Fully upholstered with foam of 70-90mm thickness, density 60kg/m³.
- Fully upholstered in fabric or leatherette.
- Beam mounted gravity tip up seat padded with foam and upholstered in fabric or leatherette.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish of at least 60 microns for indoor use and hot dipped galvanized to BS 729 for outdoor use.
- Conformity with BS-6496 hardness test.

Standards

- Horizontal beam structure of 60mm X 40mm X 3mm thk.

Upholstery Material

- Refer to Ferco standard fabric / leatherette / leather charts.

Plastic

- Refer to Ferco standard plastic charts.

Advantages

- Comfort especially studied according to fundamental criteria of ergonomic.
- Durability of the chair & after sales service for all spare parts of the model.
- Slim profile creating enhance seat way.
- Curved backrest design for maximum comfort.
- “Steel Beam Clamp” concept giving the ease of relocation of seats along the beam.
- Two piece tip-up arena, auditorium and sports venue seat. The tip-up mechanism is counter weight activated by gravity with silent operation.

Fire Safety


- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 0 & 1.

Warranty


Refer to Ferco product warranty.

Options

- ARC Multi with PU
- ARC Multi Plus
- ARC Multi with cupholder
- ARC Multi Retractable armrest (with spring)
- ARC Multi Retractable armrest (without spring)
- ARC end cap with row numbering / lettering
- ARC seat numbering
- Riser mounted leg
- Embroidery seat numbering
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 5



560 (22") 585 (23")
610 (24")



C

DIMENSIONS	
H	C
900 (35.5")	530 (21")